

Marine Hose

Redback® Wet Exhaust - Marine (Specification 4684CF)



Nom. I.D.		Nom. O.D.		Maxi. W.P.		Suction		Min. Bend Radius		Kg. Per	Standard Pack	Part No.
(In.)	(mm)	(In.)	(mm)	(psi)	(Mpa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(m.)	(m.)	
1	25.4	1.44	36.6	100	0.69	25.0	635	3.0	76	0.75	3	4684-1540
1 1/8	28.6	1.56	39.6	100	0.69	25.0	635	4.0	102	0.82	3	4684-1545
1 1/4	31.8	1.69	42.9	100	0.69	25.0	635	4.0	102	0.92	3	4684-1551
1 3/8	34.9	1.81	46.0	85	0.59	25.0	635	4.0	102	0.98	3	4684-1556
1 1/2	38.1	1.94	49.3	85	0.59	25.0	635	4.0	102	1.05	3	4684-1561
1 5/8	41.3	2.06	52.3	75	0.52	20.0	508	5.0	127	1.12	3	4684-1601
1 3/4	44.5	2.19	55.6	75	0.52	20.0	508	5.0	127	1.18	3	4684-1611
1 7/8	47.6	2.31	58.7	60	0.41	20.0	508	5.0	127	1.25	3	4684-1651
2	50.8	2.44	62.0	60	0.41	20.0	508	5.0	127	1.31	3	4684-1660
2 1/8	54.0	2.56	65.0	55	0.38	20.0	508	6.0	152	1.38	3	4684-1670
2 1/4	57.2	2.69	68.3	55	0.38	20.0	508	6.0	152	1.48	3	4684-1680
2 3/8	60.3	2.81	71.4	50	0.34	20.0	508	7.0	178	1.54	3	4684-1690
2 1/2	63.5	2.94	74.7	50	0.34	20.0	508	7.0	178	1.61	3	4684-1700
2 5/8	66.7	3.06	77.7	40	0.28	15.0	381	9.0	229	1.67	3	4684-1711
2 3/4	69.9	3.19	81.0	40	0.28	15.0	381	10.0	254	1.74	3	4684-1720
2 7/8	73.0	3.31	84.1	40	0.28	15.0	381	11.0	279	1.80	3	4684-1730
3	76.2	3.44	87.4	40	0.28	15.0	381	12.0	305	1.87	3	4684-1740
3 1/2	88.9	4.06	103.1	35	0.24	15.0	381	17.0	432	2.17	3	4684-1750
4	101.6	4.44	112.8	30	0.21	10.0	254	24.0	610	2.43	3	4684-1760
4 1/2	114.3	4.94	125.5	25	0.17	5.0	127	27.0	686	2.76	3	4684-1764
5	127.0	5.44	138.2	15	0.10	5.0	127	30.0	702	3.02	3	4684-1766
6	152.4	6.46	164.1	15	0.10	5.0	127	36.0	914	3.61	3	4684-1722

Recommended for:

The corrugated Redback® (4684CF) exceeds SAE J20R2, SAE J20R5 and SAE J2006.

It is a highly flexible hose ideal for use in marine wet exhaust and general purpose applications where tight bends are required. It is also suitable for coolant lines.

Temperature: -40°C to +100°C continuous service.

Construction:

Tube: Type C (Nitrile). Black. Oil and heat resistant.

Reinforcement: Synthetic fabric with built-in wire.

Cover: Type A (Neoprene). Black with red spiral stripe. Oil and heat resistant.


Packaging:

1", 1-1/4", 1-3/8", 1-1/2", 1-5/8", 1-7/8": Packaged 15m coiled in a carton.

4 1/2" through 6": Packaged in straight lengths in woven fibre.

All other sizes: Packaged 3m per carton.

Branding: Continuous transfer labels every 3m.

Example:  4684CF Engine Coolant-Marine Wet Exhaust 2 Inch Made In U.S.A.

Standards: Meets requirements of SAE J20R2, SAE J20R5, and SAE J2006.

Tube: RMA (Class B) Medium oil resistance.

Cover: RMA (Class C) Limited oil resistance.