



R. P. WALLIS
WHOLESALE

Truck & Industrial Spares for over 40 years

MELBOURNE

8 Park Rd, Oakleigh, VIC 3166

P.O.Box 398 Chadstone Centre, Chadstone, VIC 3148

Ph: (03) 9563 0000 Fax: (03) 9563 4000

SYDNEY

Unit 2/158 Newton Rd, Wetherill Park, NSW 2164

Ph: (02) 9756 5111 Fax: (02) 9756 5658

email: enquiries@spareco.com.au www.spareco.com.au

FUEL FILL HOSE

FEATURES & BENEFITS



Temperature Range

-40 degrees C to +100 degrees

Packaging

3 ft (0.91m) lengths

- This range is especially designed for transferring fuel from vehicle's filler neck to fuel tank
- Resistant to gasoline and diesel, gashole blends of ethanol, methanol, and ethers. (up to maximum concentration allowed by EPA)
- Corrugated cover with helical wire reinforcements.
- Features high quality nitrile tube.
- Meets requirements of SAE 30R5
- Cuts easily with a knife and wire cutters.

Part Number	Diameter (Inches)	Working Press.(PSI)
23924	1.5	20
23930	1.875	20
23932	2	20
23936	2.25	20

FUEL FILLER NECK HOSE

FEATURES & BENEFITS



Temperature Range

-40 degrees C to +100 degrees C

Packaging

3 ft (0.91m) lengths

- This range is especially designed for auxiliary tanks on recreational vehicles.
- Smooth, oil resistant cover, tough textile corrugated reinforcement and petroleum-resistant nitrile tube.
- Meets requirements of SAE 30R6
- Cuts easily with a knife and wire cutters.

Part Number	Diameter (Inches)	Working Press.(PSI)
23964	1.5	20
23968	1.75	20
23972	2	20
23976	2.25	20
23980	2.5	20

SEE OUR FULL RANGE OF PRODUCTS AT www.spareco.com.au



The most trusted name in belts & hose