



**R. P. WALLIS
WHOLESALE**

Truck & Industrial Spares for over 40 years

MELBOURNE

8 Park Rd, Oakleigh, VIC 3166

P.O.Box 398 Chadstone Centre, Chadstone, VIC 3148

Ph: (03) 9563 0000 Fax: (03) 9563 4000

SYDNEY

Unit 2/158 Newton Rd, Wetherill Park, NSW 2164

Ph: (02) 9756 5111 Fax: (02) 9756 5658

email: enquiries@spareco.com.au www.spareco.com.au

GATES FUEL LINE



FEATURES & BENEFITS

- Reinforced construction.
- Nitrile Tube and cover
- Oil resistant cover resists the effects of high heat and ozone found in engine compartments
- Not to be used for fuel injection applications

- Performs to SAE 30R6 & 30R7.
- Vacuum rating of 24 in./Hg for sizes less than 1/2" (13mm) to 3/4" (19mm) I.D. at ambient temperatures.

Temperature Range

-40 degrees C to +125 degrees C

ID (Inches)	ID (mm)	Work Press (psi)	25 Foot Length	50 Foot Length	100 Foot Length	250 Foot Length
1/8"	3.2	50	27000	-	-	-
3/16"	4.8	50	27001	-	-	-
1/4"	6.3	50	27002	27022	27062	27068
9/32"	7.1	50	27011	-	-	-
5/16"	8	50	27003	27023	27063	27069
3/8"	9.5	50	27004	27024	27064	27070
7/16"	11.1	35	27005	-	-	27071
15/32"	11.9	35	-	-	-	-
1/2"	12.7	35	27006	-	-	27019
5/8"	15.9	35	27008	-	-	27020
3/4"	19	35	27010	-	-	27021

GATES FUEL INJECTION HOSE



- Its polyester braid reinforcement increases strength.
- It has an oil, heat, ozone, and abrasion resistant cover.
- It meets SAE 30R9 requirements
- Maximum working temperature of +302 degrees F (+150 degrees C)
- Note : Fuel MTBE concentrations must not be greater than 15% by volume.

ID (inches)	ID (mm)	Work Press-psi	Part No	Part No	Part No
			(3 ft)	(10 ft)	(25 ft)
1/4"	6.3	180	27090	27082	27094
5/16"	8	180	27091	27085	27095
3/8"	10	180	27092	27088	27096

SEE A FULL RANGE OF OUR PRODUCTS AT www.spareco.com.au



**The most trusted name in
belts, hose, and hydraulics**