



**R. P. WALLIS
WHOLESALE**

Truck & Industrial Spares for over 40 years

MELBOURNE

8 Park Rd, Oakleigh, VIC 3166

P.O.Box 398 Chadstone Centre, Chadstone, VIC 3148

Ph: (03) 9563 0000 Fax: (03) 9563 4000

SYDNEY

Unit 2/158 Newton Rd, Wetherill Park, NSW 2164

Ph: (02) 9756 5111 Fax: (02) 9756 5658

email: enquiries@spareco.com.au www.spareco.com.au

STRAIGHT GREENSTRIPE HOSE



Temperature Range

-40 degrees C to +125 degrees C

Packaging

3 ft (0.9m) lengths

Caution: Do not use for fuel or oil transfer applications

FEATURES & BENEFITS

- Stick hose designed for demanding heavy-duty coolant/air applications.
- Approved for Marine Applications.
- This coolant hose has a two-ply bias fabric construction to maximize flexibility and strength.
- It resists "cold water leaks" thanks to an advanced EPDM tube that stays soft and pliable, even under adverse operating conditions.
- The hose reduces water loss from water permeating the hose wall and cover, a distinct advantage over silicone.
- It exceeds SAE 20R1 Type EC (Class D-1 Tube, and cover, Standard Wall).
- It is engineered to resist electrochemical degradation - the leading cause of hose failure.

ID (inches)	Working Pressure (psi)	Part Number
3/4"	80	24212
7/8"	75	24214
1"	125	24216
1 1/8"	100	24218
1 1/4"	100	24220
1 3/8"	100	24222
1 1/2"	100	24224
1 5/8"	85	24226
1 3/4"	75	24228
1 7/8"	75	24230
2"	60	24232
2 1/8"	60	24234
2 1/4"	60	24236

ID (inches)	Working Pressure (psi)	Part Number
2 3/8"	60	24238
2 1/2"	60	24240
2 5/8"	60	24242
2 3/4"	60	24244
2 7/8"	55	24246
3'	25	24248
3 1/8"	25	24250
3 1/4"	20	24252
3 1/2'	18	24256
3 3/4"	18	24260
4"	12	24264
4 1/2"	12	24272

SEE OUR FULL RANGE OF PRODUCTS AT www.spareco.com.au



**The most trusted name in
belts, hose, and hydraulics**