



**R. P. WALLIS  
WHOLESALE**

*Truck & Industrial Spares for over 40 years*

**MELBOURNE**

8 Park Rd, Oakleigh, VIC 3166

P.O.Box 398 Chadstone Centre, Chadstone, VIC 3148

Ph: (03) 9563 0000 Fax: (03) 9563 4000

**SYDNEY**

Unit 2/158 Newton Rd, Wetherill Park, NSW 2164

Ph: (02) 9756 5111 Fax: (02) 9756 5658

email: [enquiries@spareco.com.au](mailto:enquiries@spareco.com.au) [www.spareco.com.au](http://www.spareco.com.au)

## 90 DEGREE MOULDED HOSE

### FEATURES & BENEFITS



**Temperature Range**

-40 degrees C to +15 degrees C

**Packaging**

Single hoses

- This range is especially designed for difficult hose applications requiring sharp 90 degree bends in the hose (please contact RP Wallis Wholesale for information on additional shapes and sizes).
- Factory moulded.
- Approved for Marine Applications.
- Recommended for upper, lower, by pass, heater, and other coolant hose applications.
- Has a heat and ozone resistant cover.
- This hose is engineered to resist electrochemical degradation - the leading cause of hose failure
- Installs without buckling, bending out of shape, or straining at connections
- Meets SAE 20R4 and 20R3 Type EC class D-1 and D-2 specifications

Caution: Do not use for fuel or oil transfer applications

Part number	ID (mm)	Arm Length (mm)
02-0353	13mm	100mm
02-0354	16mm	100mm
02-0355	19mm	125mm
02-0356	24mm	125mm
05-1101	32mm	150mm
05-1102	38mm	150mm
20065	38mm	250mm
20573	38mm to 44mm	385mm
05-1103	44mm	175mm
20957	44mm	463mm
21118	44mm to 50mm	390mm

Part number	ID (mm)	Arm Length (mm)
05-1104	50mm	175mm
21379	50mm	508mm
21378	50mm	760mm
05-1105	57mm	200mm
20401	57mm	620mm
21132	57mm to 63mm	620mm
20970	63mm	422mm
21115	63mm	630mm
21042	76mm	355mm
21892	89mm	368mm

SEE OUR FULL RANGE OF PRODUCTS AT [www.spareco.com.au](http://www.spareco.com.au)



The most trusted name in  
belts & hose