

HI-TORQUE - Heavy Duty Clamps

Guaranteed to withstand more than 3 times the SAE standard torque requirements for Type F worm-drive clamps



Bigger, heavier and stronger than our premium aircraft-grade Aero-Seal

This is the original and still the highest torque rated worm-drive clamp available in the world!

Use it where conventional clamps are inadequate or in applications where double and triple clamping is now needed.

Standard Series -- (HTM - - - Series)

Made in a range of stock sizes for convenient adjustment around standard diameters (typically in OEM or other production assembly work).

STOCK NUMBERS		EFFECTIVE DIAMETER RANGE			
HTM --- Standard		Min.		Max.	
		in.	mm.	in.	mm.
HTM-175		1	25	1-3/4	44
HTM-200		1-1/4	32	2-1/8	54
HTM-250		1-3/4	44	2-5/8	67
HTM-300		2-1/4	57	3-1/8	79
HTM-350		2-3/4	70	3-5/8	92
HTM-400		3-1/4	83	4-1/8	105
HTM-450		3-3/4	95	4-5/8	118
HTM-500		4-1/4	108	5-1/8	130
HTM-550		4-3/4	121	5-5/8	143
HTM-600		5-1/4	133	6-1/8	156
HTM-650		5-3/4	146	6-5/8	168
HTM-700		6-1/4	159	7-1/8	181
HTM-750		6-3/4	172	7-5/8	194
HTM-800		7-1/4	184	8-1/8	206
HTM-850		7-3/4	197	8-5/8	219
HTM-900		8-1/4	210	9-1/8	232