

Crankcase Ventilation

CCV[®] Series



Specifications	CCV4500	CCV6000	CCV8000
Max. Flow Rate	10 CFM (283 LPM)	20 CFM (566 LPM)	40 CFM (1132 LPM)
Max. Engine Rating	400 HP (298 KW)	800 HP (597 KW)	1600 HP (1193 KW)
Height	9.3 in. (23.5 cm)	12.0 in. (30.4 cm)	13.9 in. (35.2 cm)
Opening Width	7.5 in. (19.0 cm)	11.3 in. (28.6 cm)	13.3 in. (33.6 cm)
Depth	5.6 in. (14.2 cm)	7.3 in. (18.5 cm)	9.3 in. (23.6 cm)
Weight	3.3 lbs (1.5 kg)	5.0 lbs (2.3 kg)	8.7 lbs (4.0 kg)
Service Clearance	2.3 in. (5.7 cm)	4.0 in. (10.1 cm)	5.0 in. (12.7 cm)
Low Density Element	N/A	N/A	N/A
Medium Density Element	CCV55248-06	CCV55274-06	CCV55222-06
High Density Element	CCV55248-08	CCV55274-08	CCV55222-08
Inlet/Outlet	1 3/16"-12 STOR	1 5/8"-12 STOR	1 7/8"-12 STOR
Pressure Regulator	Integral	Integral	Integral
Bypass Indicator	Integral or Remote	Integral or Remote	Integral or Remote
Return Fitting	1/4" NPT	1/4" NPT	3/8" NPT
Swivel Fitting	#6 JIC (2pcs)	#6 JIC (2pcs)	#8 JIC (2pcs)
Oil Drain Hose I.D.	0.375 in.	0.375 in.	0.5 in.
Operating Temperature	-40° to +240°F (-40 to +116°C)		