



## WORM DRIVE CLAMPS - General Purpose Industrial and Automotive Clamps

**General purpose automotive and industrial clamps.** High strength construction. Exceeds [SAE](#) requirements. Use for all standard clamp applications.

### A TURN FOR THE BETTER

The sealing pressure oriented design on Breeze Power-Seal clamps enables it to outperform other general purpose industrial clamps. **Why?**

*Because the band width to torque to sealing pressure properties of Breeze Power-Seal clamps are designed to give higher sealing pressure with lower applied torque. This is especially important in the lower, typical torque ranges achieved when a clamp is installed by hand with a screwdriver or nutdriver.*

#### 62000 Series

**Use for standard clamp applications.** Stainless steel band and housing with a carbon steel, carbon plated, slotted hex head screw.

#### 64000 Series

**For use in outdoor, fresh water, and mildly corrosive applications.** All stainless steel band, screw, saddle and housing.

STOCK NUMBERS			EFFECTIVE DIAMETER RANGE			
Plated Hex Screw		Stainless Steel Hex Screw	Min.		Max.	
			in.	mm.	in.	mm.
62006		64006	7/16	11	25/32	20
62008		64008	1/2	13	29/32	23
62010		64010	9/16	14	1-1/16	27
62012		64012	11/16	17	1-1/4	32
62016		64016	13/16	21	1-1/2	38
62020		64020	13/16	21	1-3/4	44
62024		64024	1-1/16	27	2	51
62028		64028	1-5/16	33	2-1/4	57
62032		64032	1-9/16	40	2-1/2	64
62036		64036	1-13/16	46	2-3/4	70
62040		64040	2-1/16	52	3	76
62044		64044	2-5/16	59	3-1/4	83

62048		64048	2-9/16	65	3-1/2	89
62052		64052	2-13/16	71	3-3/4	95
62056		64056	3-1/16	78	4	102
62060		64060	3-5/16	84	4-1/4	108
62064		64064	3-9/16	91	4-1/2	114
62072		64072	1-7/8	48	5	127
62080		64080	2-1/2	64	5-1/2	140
62088		64088	3-1/8	79	6	152
62096		64096	3-5/8	92	6-1/2	165
62104		64104	4-1/8	105	7	178
62128		64128	5-5/8	143	8-1/2	216
62152		64152	7-1/8	181	10	254
62188		64188	9-3/8	238	12-1/4	311
<i>* Larger &amp; custom sizes available upon request.</i>						